

Pti-8411G Wireless Security Set Up Instruction

ADSL2/2+ Router

ADSL2/2+ Router

Home Home Setup Wizard Tools **Advance** SAVE

1. Click on 'Advance'.

System

Model Name: 8411G
System UpTime: 21:57
Software Version: 84110_ETC_100507.00FA
UI Version: 1.002
Firmware Version: 1.3.8
DSP Version: 2.8.0.2

DSL

DSL Status: SHOWTIME G.dmt
Upstream Speed: 832 kbps (interleave)
Downstream Speed: 7904 kbps (interleave)

LAN

IP Address: 192.168.1.1
Subnet Mask: 255.255.255.0
DHCP Server: Enabled
MAC Address: 00e04c967001

WAN

Interface	VPWCI	Encap	IP Address	Gateway	Status
Talk Talk	038	PPPoA_VCMUX		195.166.128.72	up 21:57:04 / 21:57:04 Disconnect

Default GW: 195.166.128.72

2. Click on 'Wireless';

Advance **WAN** LAN **Wireless** Router Firewall Status Home **SAVE**

WAN ATM ADSL

Channel

VPI :

VCI :

Encapsulation: LLC VC-Mux

Channel Mode:

NAPT:

Admin Status: Enable Disable

PPP

User Name:

Password:

Connection Type:

Idle Time (min):

WAN IP

Type : Fixed IP DHCP

Local IP Address:

Subnet Mask:

Remote IP Address:

DNS 1:

DNS 2:

DNS 3:

Unnumbered:

Default Route: Disable Enable

Current ATM VC Table

Select	Inf	Mode	VPI	VCI	Encap	NAPT	DRoute	Status	Actions
<input type="radio"/>	ppp0	PPPoA	0	38	VCMUX	On	On	Enable	

Advance WAN LAN **Wireless** Router Firewall Status Home **SAVE**

Setting **Security** Access Control WDS

3. Click on 'Security'.

Security

Encryption:

4. Select the encryption type from the drop down list.

Authentication Type: Open System
 Shared Key
 Auto

802.1x Enabled
 WEP 64bits WEP 128bits

WPA Authentication Mode: Enterprise (RADIUS)
 Personal (Pre-Shared Key)

Pre-Shared Key Format:
Pre-Shared Key:

5. Enter the pass key (8 ~ 64 characters) in the box

RADIUS Server: Port
IP address
Password

6. Click on the 'Submit' button.

Note: When encryption WEP is selected, you must set WEP key value.

Advance WAN LAN **Wireless** Router Firewall Status Home **SAVE**

Setting Security Access Control WDS

8. Click on 'Save'.

Security

Encryption: WPA (TKIP)

Authentication Type: Open System
 Shared Key
 Auto

802.1x Enabled:

WPA Authentication Mode: Enterprise (RADIUS)
 Personal (Pre-Shared Key)

Pre-Shared Key Format: Passphrase

Pre-Shared Key:

RADIUS Server: Port:
IP address:
Password:

Note: When encryption WEP is selected, you must set WEP key value.

Advance WAN LAN **Wireless** Router Firewall Status Home **SAVE**

Setting Security Access Control WDS

Security

Er

Aut



9. Click on the 'OK' button to complete the process.

Home Home Setup Wizard Tools Advance **SAVE**

Done

Process done, return [Home](#)